COVID-19 NEGATIVE PRESSURE SWAB BOOTH



TEST CERTIFICATION Covid-19 Booth Exhaust HEPA Filter Integrity Report Nos: IST262/0520

STANDARD INSPECTION TEST EN1822 Class H11/H12/H13/H14 IES RP-CC-001.3 TYPE A/B/C/D Mini Pleat STD. Capacity HEPA Filter

ELECTRICAL CERTIFIED Electrical Installation Profession Engineer Certified

CERTIFCATION WILL BE PROVIDED UPON REQUEST BY THE BUYER AND AUTHORITY

Imported material (Booth is Made in Singapore)

Catalogue number: C19-NPSB-800-2020

Overview

This COVID-19 Negative Pressure Swab Booth (MODEL: C19-NPSB-800) is designed and MADE IN SINGAPORE for the world market for Covid-19 swab test use. This booth is for an individual to perform a self nasal swab / collect oral fluid in a safe and controlled environment for COVID-19 RT-PCT Test. The booth is designed for both indoor and outdoor application. All electrical components and connections on the booth exterior are weatherproof type. Room exhaust is achieved via a low level exhaust grille that is connected to a G4 + HEPA (99.99% filtration efficiency at 0.3µm) filter module and exhaust fan for safe discharge of booth air back to the environment. Our filter unit is design to ensure safe and easy filter change without compromising the safety of the maintenance personnel and contaminate the environment.

Features

Each HEPA filter unit has passed integrity and filter module leak tests using internationally recognised procedures not exceeding 0.005% penetration. A two-way intercom system is incorporated for communication between the healthcare worker or workers outside the booth and the individual inside. The booth and filter unit is installed with 2 de-containment ports for connection to a vaporised hydrogen peroxide generator for fumigation. Smooth and impervious surfaces which is chemical resistant to alcohol, bleach and hydrogen peroxide based disinfectant for easy wipe-down.

Single piece sturdy design for easy transportation. Base come with levelling studs and castors wheels. Weatherproof Magnehelic Gauge displaying the booth and filter unit differential pressure status allow easy reading by a healthcare worker.

Negative Swab Booth Specification

- Internal dimensions Structure
- : 1000mm (Width) x 1200mm (Depth) x 2100mm (Height)
 - : Anodized aluminium.
- : Chemical resistant polypropylene (PP) and clear PVC.
- : 18mm thick chemical resistant phenolic.

EXCLUSIVE DISTRIBUTOR & MARKETING AGENT:

Securitex Electronic Systems Engineering Block 9010 Tampines Street 93 #04-145 Tampines industrial Park A. singapore 528844 Tel : 67852171 Fax: 65850107 E: <u>sales@securitex.com.sg</u> Website : www.securitex.com.sg THIS DRAWING IMAGES AND CONTAINED INFORMATION IS COPYRIGHTED & IS THE EXCLUSIVE PROPERTY OF WHOLESEOME.. THIS DRAWING AND IMAGE IS BEING CLOSED CONFIDENTIALLY. IT MAY NOT BE REPRODUCED OR DISCLOSED OR GIVEN IN WHOLE OR IN PART TO ANY OTHER PARTY FOR ANY PURPOSED OTHER THEN MARKETING WITH PERMISSION AND ANY USED OF THIS INFORMATION IS SUBJECT TO GIVEN WRITTEN PERMISSION BY THE MANUFACTURER & THE MARKETING AGENT IN SINGAPORE.