

Video Sentry PanTilt

DOOR

3

ROOM

3

MY-2CD

+)))

🔑

- Dual PanTilt doors & three monitors
- Additional audio door station
- Two door release buttons (MY-2C2D only)
- All-call type room calling

MONOCHROME

PANTILT

New


MK-DBC
Video door station
→ P.29


MK-DAC
Video door station


IF-DA
Door station


MY-2CD
Master station


MYH-2CD
Sub master station


MY-1HD
Sub master station


KC-32EU
Picture memory unit
→ P.32


MYW-BA
Long distance adaptor
→ P.33


RY-3DL
Door release adaptor

KAW-D 30° Angle Box → P.33

EL-9S Door release → P.97

IER-2 Call extension → P.96

MCW-S Desk-top stand → P.33

Communication network & wiring

- Door release (K)2: available with RY-3DL
- Door station IF-DA is optional for third entry

- MY-1HD can be wired in the same manner as MYH-2CD. (Read 1A1, 1A2 terminals each as A1, A2) (K) 6 wires when +, - wires are doubled.

System components

- MK-DBC:** Video door station (any MY, MK)
- MY-2CD:** Master station
- MYH-2CD:** Sub master station
- MY-1HD:** Sub master station (Audio only)
- RY-3DL:** Door release adaptor
- 18V DC power supply: PS-18E**

Specifications (MY-2CD)

Power source	18V DC, 1.96A. 0.28A standby	
Power supply	PS-18E	
Video monitor	4" direct view flat CRT	
Scanning line	525 lines	
Communication	Door calls in w/4, 2 or 8-tone chime 45 sec. timed. Lift any handset to reply 2-1/2 min. timed. Press ROOM to call the rest stations with tone & voice.	
Wiring	2 wires parallel to door, non-polarized. 4 or 6 (or 6 or 8) wires, rooms	
Wiring distance	0.65mmø	1.0mmø
• MY-2CD ~ P/T door	50m	100m
• MY-2CD ~ MY-DS	100m	200m
• MY-2CD ~ IE/IF	150m	360m
Room monitors	1.0mmø	1.0mmø (*)
• MY-2CD ~ MYH1	56m	75m
• MY-2CD ~ MYH1-2	28m	56m

(*) +, - wires doubled.

24

25