

Smart wing-Flap Gate



Securitex WG170

The Securitex Smart wing flap gate "Model Securitex WG170" is designed for high human traffic environment. This system is design and manufactured with high quality material to ensure long term reliability and virtually no or minimum operation down time. This Flap Gate is very suitable to be used in Airport. Military base. Oil and Gas facilities, Custom and immigration checkpoint, Mass Rapid Transit facilities etc...

Model	SECURITEX WG170
Dimension	1400mm X 280mm X 1090mm (Passage width 520mm)
Make	Securitex Single/Double smart wing Gate
Product description	<ol style="list-style-type: none">1. Single Core Machine Box for single passage direction2. Double Core Machine Box for multi-passage direction3. Passage extent up to 520 mm4. Appearance Sizes 1400mm X 280mm X 1090mm5. Power requirement: AC230AC/50HZ6. Working Environment : -15centigrade to 60centigrade (indoor)7. Relative humidity: 90%8. Input port:<ol style="list-style-type: none">a. more than 10ms 12V impulse signalb. Drive electrical current: more than 10mA9. Communication port: :RS48510.Communication distance: 1200m11.Transit Speed: 50 person/minute12.Opening /Shutting down time:1 second

Distributed and marketed by
Securitex Electronic Systems Engineering
Block 9010 Tampines St 93 #04-145 Tampines Industrial park A Singapore 528844 Tel: 65-67852171 Fax:
65-67863351 <http://www.securitex.com.sg>