

Securitex Kocom intercom division



- 3.5" TFT LCD Display
- Max. 2 Monitors parallel connectable with a camera
- 4 Wired in polarity
- Wide view angle 90°
- Door release function
- Door release from Camera
- Hands-Free type
- Easy installation
- KCV-350: AC 220V Power Built-in(50 or 60Hz)/KCV-D350 : DC 18V(50 or 60Hz)

Item	Specification
Monitor	KCV-350 / KCV-D350
Power	KCV-350 : AC 220V / KCV-D350 : DC 18V
Power consumption	Max 8W, Stand by 1W
Assurance temperature	0 ~ 50°C
Communication system	One Way Hands-free
TFT LCD	3.5" Color TFT LCD
Wiring	4 Wired in polarity
Max Wiring Distance	0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	310(W) X 240(H) X 15(D) mm
Door Camera	KC-D32
Power	DC 12V ±1V (Power from monitor)
Power consumption	Max 3W
Assurance temperature	-10°C~50°C
Image Sensor	1/3" CCD (270,000/320,000 Pixels)
Scanning Frequency	Horizontal 15,625 KHz or 15,732 / Vertical 50Hz or 60Hz
Lens	F:20, f=3.0mm
Minimum illumination	10Lux (LED ON)
Installation	Embedment Type
Dimension	95(W) X 127(H) X 46(D) mm

Marketed and distributed by

Securitex Electronic Systems Engineering
 Block 9010 Tampines Street 93 #04-145 Singapore 528844 Tel: 65-67852171 Fax: 65-67863351
<http://www.securitex.com.sg>