

## Securitex Kocom intercom division



### **KIV-101**

For Multiple Families, Villa, Mansion & Apartment

4" B/W Flat Monitor

Hands-free System

Communication

- Monitor to Door Camera

- Monitor to Guard Office Interphone (Audio only)

4 Wired in polarity

Door Release Function

Wide view angle

- Wide view angle(120°)not necessary to adjust camera view angle

- Clean picture through circuit of image compensation in bright back light

Easy Installation

Power AC 110V or 220V

DC Type Available

Item	Specification
MONITOR	<b>KIV-101</b>
Power	TRANS Type(AC 220V or 110V, 50 or 60Hz)
Power consumption	Max 15W, Stand by 1W
Assurance temperature	0 ~ 50°C
Communication system	One Way Hands-free
Brawn Tube	4" inch flat tube
Wiring	4 Wired in polarity
Max Wiring Distance	Ø0.65 Single Cable/50m, 5C-2V Coaxial Cable 100m
Dimension	190(W) X 216(H) X 51(D)mm
DOOR CAMERA	KC-C61 / KC-D30 (Metal Pinhole Camera)
Power Source	DC 12V±1V (Power from monitor)
Power consumption	Max 3W
Assurance temperature	-10 ~ 50°C
Camera (Image Device)	1/3" CCD (270,000 / 320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,734KHz / Vertical 50Hz or 60Hz
Lens	F:2.0, f=3.0mm
Minimum illumination	0.1Lux on the object (IR LED ON)
Dimension	95(W) X 127(H) X 34(D) mm

### **Marketed and distributed by**

Securitex Electronic Systems Engineering

Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351

<http://www.securitex.com.sg>