

## Securitex Kocom intercom division



For Multiple Families, Villa, Mansion & Apartment

4" Color LCD Monitor

Hands-free System

Communication

Monitor to Door Camera - Monitor to Guard Office Interphone (Audio only)

4 Wired in polarity

Door Release Function

Wide view angle

- Wide view angle(120°)not necessary to adjust camera view angle
- Clean picture through circuit of image compensation in bright back light

Easy Installation

Power AC 110V or 220V

DC Type Available

Item	Specification
MONITOR	<b>KIV-201C</b>
Power	SMPS TYPE(AC 220V or 110V, 50 or 60Hz)
Power consumption	Max 19W, Stand by 2W
Assurance temperature	0 ~ 50°C
Communication system	One Way Hands-free
TFT LCD	4" Color TFT LCD
Wiring	4 Wired in polarity
Max Wiring Distance	Ø0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	(W)237 X (H)199 X (D)39 mm
DOOR CAMERA	KC-C60 / KC-D31
Power Source	DC 12V ±1V (Power from monitor)
Power consumption	Max 2W
Assurance temperature	-10°C ~ 50°C
Camera(Image Device)	1/3" CCD (270,000 / 320,000 Pixels)
Scanning Frequency	Horizontal 15,625Khz or 15,734Khz / Vertical 50Hz or 60Hz
Lens	F:2.0, f=2.9mm
Minimum illumination	0.1Lux on the object (LED ON)
Dimension	(W)95 X (H)127 X (D)34 mm

### **Marketed and distributed by**

Securitex Electronic Systems Engineering

Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351

<http://www.securitex.com.sg>