

Securitex Kocom intercom division



KVM-520

- Multiple-entry video door-phone For Multiple Families, Villa, Mansion & Apartment
- Communication with Guard
- 4" CRT Monitor
- Max. 3Monitors Parallel Connectable with 1 Camera
- Easy Installation
- Power : Built-in AC 110V or 220V
- Door Release Function
- Can be combined with door opener(DO-12/option)

Item	Specification
Monitor	KVM-520
Power	Built-in AC 220V or 110V / DC 17V
Power consumption	Max 15W, Stand by 2W
Assurance temperature	0 ~ 50°C
CRT	4 inch (B/W)
Communication	Duplex Handset Conversation
Call signal sound	Tone
Output Impedance	Picture:75ohm, Voice:600ohm
TV System	EIA or CCIR
Body Color	White
Dimension	210(W) X 222(H) X 57(D)mm
Camera	KC-D20
Power	DC12±1V (power from monitor)
Power consumption	Max 3W
Assurance temperature	-10°C ~ 50°C
Camera(Image Device)	1/3"CCD (270,000/320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,732KHz / Vertical 50Hz or 60Hz
Lens	F:2.0, f=3.0mm
Minimum illumination	0.1Lux on the object(IR LED ON)
Illumination	Infra-red LED
Angle of picture	Diagonal 120°
Dimension	95(W) X 127(H) X 32(D)mm

Marketed and distributed by

Securitex Electronic Systems Engineering

Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351

<http://www.securitex.com.sg>