

Securitex Kocom intercom division



- Easy Installation & High Quality, 4 Wired Series Intercom Function
- 4" Flat Monitor
- Max. 3Monitors Parallel Connectable with 1 Camera
- 4 Wired in polarity
- Easy Installation
- Wide View Angle (Metal Pinhole Camera 90°)
- Not necessary to adjust camera view angle
- Power AC : 110V or 220V (KVM-524G) / DC : 17V External Adapter (KVM-514G)
- Door Release Function
- Can be combined with door opener(DO-12/option)

Item	Specification
MONITOR	KVM-524G / KVM-514G
Power	Built-in AC 220V or 110V (KVM-524G) / DC 17V External Adapter (KVM-514G)
Power consumption	Max 18W, Stand by 2.3W
Assurance temperature	0 ~ 50°C
CTR tube	4 inch Flat Tube(B/W)
Communication	Duplex handset conversation
Call signal sound	Electric sound(Ding-dong)
Output Impedance	Picture:75ohm, Voice:600ohm
Wiring	4 Wired in polarity (VCC/GND/VOICE/PICTURE)
Max Wiring Distance	Ø0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	210(W) X 222(H) X 57(D)mm
Camera	Power DC12±1V (power from monitor)
Power consumption	Max 3W
Assurance temperature	-10°C ~ 50°C
Camera(Image Device)	1/3"CCD (270,000/320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,732KHz / Vertical 50Hz or 60Hz
Lens	F:20., f=3.0mm
Minimum illumination	0.1Lux on the object(IR LED ON)
Illumination	Infra-red LED
Angle of picture	Diagonal 90°
Dimension	95(W) X 127(H) X 32(D)mm

Marketed and distributed by

Securitex Electronic Systems Engineering

Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351

<http://www.securitex.com.sg>