

Securitex Kocom intercom division



KVM-524RG / KVM-514RG

Easy Installation & High Quality, 4 Wired Series
 64 Image Memory
 2 Monitors connection with 2 Cameras
 Intercom Function
 Easy Installation
 4 Wired in polarity
 4" Flat Monitor
 Wide View Angle - Not necessary to adjust camera view angle
 Door Release Function - Can be combined with door opener(DO-12/option)

Item	Specification
Monitor	KVM-524RG / KVM-514RG
Power source	POWER AC 110 or 220V (KVM-524RG) / DC 17V (KVM-514RG)
Power consumption	Max 15W, Stand by 2.5W
Assurance temperature	0 ~ +50°C
CTR tube	4 inch Flat Tube(B/W)
Communication	Duplex handset conversation
Call signal sound	Electric sound(Ding-dong)
Output Impedance	Picture:75ohm, Voice:600ohm
Wiring	4 Wired in polarity (VCC/GND/VOICE/PICTURE)
Max Wiring Distance	Ø0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	210(W) X 222(H) X 57(D)mm
Camera	KC-D20(Metal Pinhole Camera) / KC-B63(Angle Adjustable Camera)
Power source	DC12±1V (power from monitor)
Power consumption	Max 2.5W
Assurance temperature	-10°C ~ 50°C
Scanning Frequency	Horizontal 15,625KHz or 15,734KHz / Vertical 50Hz or 60Hz
Lens	F:2.0, f=3.0mm
Minimum illumination	0.1Lux on the object (LED ON)
Illumination	Infra-red LED
Angle of picture	Diagonal 90° (KC-D20) / 120° (KC-B63)

Marketed and distributed by

Securitex Electronic Systems Engineering
 Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351
<http://www.securitex.com.sg>