

Securitex Kocom intercom division



KVM-604

Easy Installation & High Quality, 4 Wired Series

SMPS Type(Dual 110V ~ 220V)

4" CRT Monitor

Easy Installation

Max. 3Monitors Parallel Connectable with 1 Camera

4 Wired in polarity

Wide View Angle 120° - Not necessary to adjust camera view angle

Door Release Function - Can be combined with door opener(DO-12/option)

Item	Specification
MONITOR	KVM-604
Power source	Built-in AC 110V~220V Free Voltage
Power consumption	Max 15W, Stand by 2W
Assurance temperature	0 ~ +50°C
Braun tube	4 inch flat Tube(B/W)
Communication	Duplex handset conversation
Wiring	4 Wired in polarity (Included power, voice, picture)
Max Wiring Distance	Ø0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	204(W) X 210(H) X 53(D)mm
CAMERA	KC-B61 / KC-D20 (Metal Pinhole Camera)
Power source	DC12±1V (power from monitor)
Power consumption	Max 2.5W
Assurance temperature	-10°C ~ +50°C
Camera(Image Device)	1/3"CCD (270,000/320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,734KHz / Vertical 50Hz or 60Hz
Lens	F:2.0, f=3.0mm
Minimum illumination	0.1Lux on the object(IR LED ON)
Dimension	95(W) X 127(H) X 32(D)mm

Marketed and distributed by

Securitex Electronic Systems Engineering

Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351

<http://www.securitex.com.sg>