

Securitex Kocom intercom division



Easy Installation & High Quality, 4 Wired Series
 SMPS Type(Dual 110V ~ 220V)
 4" CRT Monitor
 Easy Installation
 2 Monitors connection with 2 Cameras
 4 Wired in polarity
 Wide View Angle 120° - Not necessary to adjust camera view angle
 Door Release Function - Can be combined with door opener(DO-12/option)

Item	Specification
MONITOR	KVM-624
Power	Built-in AC 110V~220V Free Voltage
Power consumption	Max 19W, Stand by 5W
Assurance temperature	0 ~ 50°C
Braun tube	4 inch Flat Tube(B/W)
Output Impedance	Picture : 75ohm, Voice : 600ohm
Wiring	7 Wired in polarity (Monitor to Monitor)
Max Wiring Distance	Ø0.65 Single Cable/50m, 5C-2V Coaxial Cable / 100m
Dimension	204(W) X 210(H) X 53(D)mm
CAMERA	KC-B62 / KC-M62 (KC-B62+Metal Cover)
Power	DC12±1V (power from monitor)
Power consumption	Max 2.5W
Assurance temperature	-10°C ~ +50°C
Camera(Image Device)	1/3"CCD (270,000/320,000 Pixels)
Scanning Frequency	Horizontal 15,625KHz or 15,732KHz / Vertical 50Hz or 60Hz
Lens	F:20., f=3.0mm / 120°
Minimum illumination	0.1Lux on the object
Dimension	95(W) X 127(H) X 32(D) (KC-B62) / 124(W) X 186(H) X 36(D)mm (KC-M62)

Marketed and distributed by

Securitex Electronic Systems Engineering
 Block 9010 Tampines Street 93 #04-145 Singapore528844 Tel: 65-67852171 Fax: 65-67863351
<http://www.securitex.com.sg>