

# EP 4BDX

## 4-channel b/w duplex multiplexer



### Specifications

**Video format:** CCIR

**Video input:** 4 inputs with loop-through, 1 Vp-p, 75 Ohm

1 VCR input, 1 Vp-p, 75 Ohm

**Video output:** 4 loop-through outputs 1 Vp-p at 75 Ohm

**Monitor output:** 1 x main monitor, 1 x call monitor

**VCR output:** multiplexed, 1 Vp-p at 75 Ohm

**Resolution:** 960 x 576

**Refresh rate:** 50 fields / sec.

**VCR playback:** full screen / quad screen

**Time-lapse recording:** adjustable

**Title:** 8 characters title generator for each camera

**Timer:** built-in real time clock

**Buzzer:** yes

**Alarm input:** 4 alarm inputs, 1 alarm reset input

**Alarm output:** 1 NO/NC relay output

**Freeze function:** yes

**Video loss detection:** yes

**Setup:** on-screen

**Sequential switch:** programmable auto sequential switch  
with adjustable dwell time (1 ~ 99 sec.)

**Key lock:** yes

**Remote control:** 9-pin Sub-D / RS-232

**Power source:** 24 V AC, 230 V AC via included power supply

**Power consumption:** 17 W max.

**Operating temperature:** 0°C ~ +50°C

**Dimensions:** 438 (W) x 44 (H) x 262 (D) mm

**Weight:** 4,5 kg