

# Auto Switcher/ Auto Switcher with alarm

## FH7144/FH7148/FH7144A/FH7148A



### SPECIFICATIONS

	FH7144	FH7148	FH7144A	FH7148A
Product name:	4 channel auto switcher	8 channel auto switcher	4 channel auto switcher with alarm	8 channel auto switcher with alarm
Video input:	4 BNC connectors	8 BNC connectors	4 BNC connectors	8 BNC connectors
Signal input:	0.7~2.0Vp-p/75ohm			
Video output:	2 BNC connectors			
Signal output:	1.0Vp-p/75ohm			
Sequencing interval:	0.5~30 seconds adjustable			
Hum and noise:	Greater than 55 dB down ( reference 0dB-1Vrms) video switching			
Switching:	3-Position toggle: by pass, auto and home ; snap-action			
Dwell time switching:	Rotary controlled, 0.5 to 30 seconds			
Alarm input:	N/A		Normal open for sensor	
Alarm output:	N/A		Build in buzzer and relay (NO/NC) output	
Reset control:	N/A		Auto/ Manual selectable	
Alarm time:	1~90 seconds adjustable			
Audio connectors:	Available for FH7144S	Available for FH7148S	N/A	
Dimension (WxDxH):	310 x 243 x 44.7 mm		441 x 243 x 44.7mm	
Weight::	N.W./G.W.:2.25 kg/2.5kg		N.W./G.W.:3 kg/3.4 kg	
Power source:	AC 120V/50Hz or AC 230V/60Hz			
Power consumption:	5W			
Operation temperature:	-10℃ ~+ 45℃			