


## Securitex Digital Surveillance Technology Division



### 4CH MPEG-4 Digital Video Recorder

AVC781, 4 CH MPEG-4 real time Digital Video Recorder. It includes features such as MPEG-4 compression format, superior real time performance with 120 IPS (NTSC) / 100 IPS (PAL), USB backup function, advance motion trigger recording, and pentaplex functions. All the benefits of this product are created to secure your life every time and everywhere.



### MPEG4 DVR Technology

Compression format provides crystal clear image with real time performance

### Multiplex

Allow live display, record, playback, backup and network operation at the same time

### Long HDD Hours

500GB HDD can record more than 60 days. (4CH, CIF Best Quality, 30IPS)

### Backup Function

Backup files with USB device and network remote recording & backup

### Remote Surveillance:

Remote surveillance with licensed software AP and IE browser  
Web surveillance supports 5 users simultaneously  
Cross-Platform Operation via IE Browser<Windows, Linux, Mac>

### Intelligent Motion Trigger Recording:

With advanced motion detection function, scheduled motion detection recording (4 different adjustable factors for motion detection sensitivity) and convenient search function, customized security environment is achieved  
Alarm trigger recording will send alert with images to designated e-mail and FTP address  
Supports pre-alarm recording (8MB)

### Covert Recording

A mask replaces the live image with a blank screen & the monitor shows nothing but recording is still on

### A/V Support

Supports 2 audio-in, 1 audio-out to record sounds  
Supports VGA output to monitor (optional)

### General:

Support multi-language OSD  
System auto recovery after power reconnected  
Support daylight saving function  
Support manual / timer / motion / alarm / remote recording functions  
Watermark function ensures authentication of recorded images  
Support TCP/IP, PPPoE, DHCP and DDNS network connection

### Securitex Electronic Systems Engineering

Block 9010 Tampines St 93 #04-145 Tampines Industrial Park A Singapore 528844 Tel: 65-67852171 Fax: 65-67863351  
<http://www.securitex.com.sg>

## Securitex Digital Surveillance Technology Division

### System Specification

<b>MODEL</b>	<b>AVC781</b>
<b>Maximum Recording Rate</b>	Frame: 720 x 480 pixels with 30 IPS (NTSC) / 720 x 576 pixels with 25 IPS (PAL) CIF: 352 x 240 pixels with 120 IPS (NTSC) / 352 x 288 pixels with 100 IPS (PAL)
<b>Adjustable Recording Speed</b>	Frame: 30, 15, 7, 3 IPS <NTSC> / 25, 12, 6, 3 IPS <PAL> CIF: 120, 60, 30, 15 IPS <NTSC> / 100, 50, 25, 12 IPS <PAL>
<b>Image Quality Setting</b>	Best, High, Normal, and Basic
<b>Hard Disk Storage</b>	IDE type, ATA66, supported HDD*1, support HDD capacity over 400GB
<b>HDD Quick Cleaning</b>	Quick clean up the "index system" of the recorded files. 250GB under 2 seconds
<b>Recording Mode</b>	Manual / Timer / Motion / Alarm
<b>Refresh Rate</b>	120 IPS for NTSC / 100 IPS for PAL
<b>Audio I/O</b>	2 audio inputs, 1 audio output (Mono)
<b>Motion Detection Area</b>	16 x 12 grids per camera for all channels
<b>Motion Detect Sensitivity</b>	4 adjustable variables with precise calculation for motion detection
<b>Pre-alarm Recording</b>	Yes (8MB)
<b>USB Interface</b>	Support USB 1.1/ 2.0 device
<b>Backup Device</b>	USB 1.1 / 2.0 backup device and network remote backup
<b>Web Transmitting / Compression Format</b>	Motion JPEG
<b>Ethernet</b>	10/100 Base-T. Support remote control and live view via Ethernet.
<b>Web Interface</b>	Support licensed software AP, and IE browser
<b>Remote Alarm Notification</b>	E-mail images, and images uploading to FTP site's specific account
<b>Network Connection</b>	Support TCP/IP, PPPoE, DHCP and DDNS function
<b>PTZ control</b>	Support PELCO-D protocol
<b>Dwell Time (Sequential Channel Switch)</b>	Programmable with adjustable dwell time
<b>Alarm I/O</b>	4 inputs, 1 output
<b>Digital Zoom</b>	Yes
<b>Key Lock</b>	Yes
<b>Video Loss Detection</b>	Yes
<b>Camera Title</b>	Support up to 6 letters
<b>Video Adjustable</b>	Hue / Color / Contrast / Brightness
<b>Date Display Format</b>	YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off
<b>Power Source</b>	DC 19V
<b>Power Consumption</b>	< 42 W
<b>Operating Temperature</b>	10° C ~ 40° C (50° F~104° F)
<b>Dimensions (mm)</b>	343mm (W) x 59mm (H) x 223mm (D)
<b>System Recovery</b>	System auto recovery after power reconnected
<b>Optional Peripheral</b>	VGA connector