

DENGEN large rapid charger with HR-MAX100

**INDUSTRIAL
DENGEN HR-MAX100
100amp max charging amps**

[Main specifications]

- type name : HR-MAX100
- single-phase input : (4 P plug with, can be drawn from the three-phase circuits).
- AC input : 200-220 V **Single phase** 50 / 60 Hz 4.0 KVA 20 A
- Rectification : Both waves rectifying system SILICON DIODE UNIT
- DC output : **12-24 V** 0 ~ **100A** Maximum **80A** Continuous
- Timer : 0 to 60 minutes (wind-up), interaction continued
- Safety devices : -200A S.C.R reverse connection protection relays (with buzzer) [output]
-Overload circuit breaker current (automatic return type) [input]
- Use (battery charging) gasoline vehicles : Rapid charger & common for both charging and Starter auxiliary large diesel and
- Dimensions and weight : Height 740 mm x width 430 mm x depth 310 mm / 48 kg
- Insulation : A kind double-insulated scheme
- * Accessories : Power cord 6 m, ± 3.2 m charging cable with

[Feature]

- Is a fully double-insulated from worrying short circuit or electric shock.
- Have a reverse connection to prevent buzzing.
- Rain resistant utility model patent full-proof structure.
- Is the lighting apparatus with meter dials are clearly seen in the dark.
- lamp is from charging at a glance reveals.



SPECIFICATION

SECURITEX ELECTRONIC SYSTEMS ENGINEERING

BLOCK 9010 TAMPINES STREET 93 #04-145 TAMPINES INDUSTRIAL PARK A SINGAPORE 528844 T: 67852171 F: 65850107 [HTTP://WWW.SECURITEX.COM.SG](http://www.securitex.com.sg) SALES@SECURITEX.COM.SG