

DENGEN Booster and Normal charge with HR-MAX70D Built in safety polarity system.

**INDUSTRIAL
DENGEN HR-MAX70D
70amp max charging amps**

[Main specifications]

- Type name : High Rate Max 70D (**HR-MAX 70D**)
- AC input : 200-220 V **Single phase** 50 / 60 Hz 1.4 KVA
- Rectification : SILICON DIODE UNIT FOR FULL WAVE RECTIFICATION
- DC output : 6-12V 70A MAX. 50A RATING or 18-24V 35A MAX.25A RATING
- Protective devices : Relay for preventing connecting error (with warning buzzer). Over current circuit breaker automatic reset.

- Applications (as battery charger) : Quick charge scooters – regular auto (24-60AH)
Normal charge scooters-diesel engine vehicle (24-120AH)
- Dimensions and weight : Height 740 mm × width 430 mm x depth 310 mm / 32 kg
- Insulation : Class A double-insulated.

- * Accessories : Power cord 6 m, ± 2.2 m charging cable with

[Feature]

- Is a fully double-insulated from worrying short circuit or electric shock.
- Have a relay for preventing connection error and built in over current circuit breaker.
- Is the lighting apparatus with meter dials are clearly seen in the dark.



SPECIFICATION

SECURITEX ELECTRONIC SYSTEMS ENGINEERING

BLOCK 9010 TAMPINES STREET 93 #04-145 TAMPINES INDUSTRIAL PARK A SINGAPORE 528844 T: 67852171 F: 65850107 [HTTP://WWW.SECURITEX.COM.SG](http://www.securitex.com.sg) SALES@SECURITEX.COM.SG