

Making a Remarkable Entry ...

... Just Got Easier.



ENTERPHONE SOLO™

The Enterphone Solo™ provides the latest in convenient door intercom for any single residential or commercial intercom application.

- Answer the door from any phone
- Open doors or gates
- In-Home paging and intercom
- Optional Built-in Cameras
- Up to 2 door stations can be connected to each controller

ENTERPHONE SOLO™ Accessories & Upgrades

ENTERPHONE SOLO™

Answer the Door From Any Phone



The Enterphone Solo provides the latest in convenient door communications for any single residential or commercial intercom application. Using the Enterphone Solo is easy. When you hear the distinctive ring you simply pick up any phone and you are automatically connected to the door. The unit is compatible with cordless phones to allow

you to answer the door from anywhere in your house or even outside.

The Enterphone Solo comes with built-in call waiting to allow you to answer the door and return to an outside call. A second door station release can also be connected to the control unit if desired. If you want to turn off the Enterphone Solo for any reason you simply unplug the controller.

If someone knocks at the door, instead of pressing the button, you can still communicate by picking up any phone and calling into the door station.

Whole House Paging and Intercom

The 421-600 intercom module can be used to page or call other residents from any phone.

Open Doors or Gates at the Touch of a Button

If you have an electric lock or gate you can use the optional activator to press the * button on your phone to let your visitor in. You can also call into the Enterphone Solo to open the gate even when not using the intercom.

Easy to Install

The Enterphone Solo requires only two wires for installation, making an upgrade from an existing doorbell extremely simple. Developers have the option of prewiring for a doorbell but using the same wires for owners who would prefer the Enterphone Solo.

Door Controller



421-200

The 421-200 Solo Door Controller supports 2 independent door stations. It interconnects to house wiring at the telephone company termination point. A 110VAC plug powers the controller as well as accessories.

Optional Modules



421-300 Output Module

The 421-300 provides a dry contact closure by pressing "*" on any phone to operate door strikes, gate motors, or any electrical device requiring a trigger. One required for each door station.



421-350 Input Module

The 421-350 provides a 1 second dry closure when the door station button is pressed. Applications include simultaneous door chimes activation or a strobe for the hearing impaired.



421-600 Intercom Module

The 421-600 provides in-home intercom by pressing "flash" then "7" on one phone to ring other phones in the house.

Door Stations



421-100 is a plastic door station for standard wall mounting.

421-150 is a brass door station that flush mounts to a double gang electrical box.

421-275 is an aluminum door station that mounts to a double gang electrical box.

Other metal door stations are available to fit existing intercom backboxes. Please call.

Optional Video



Most Solo door stations can be fitted with a color or B/W video camera. These can be used to view visitors on monitors or run through modulators to your TV. A video/usb converter can also be used to record video on your PC. Separate power required.

Specifications

Plastic Door station	3 6/8" w x 5 1/8" h x 1" d
Metal Door stations	double gang flush box required
Controller	5 6/8" w x 3 7/8" h x 1 6/8" d
Door Release	4 7/8" w x 3 1/8" h x 1 2/8" d
Wire Requirements	min. 18 gauge LVT 2 conductor

For product specifications call your Viscount Representative.

Call Toll Free **1-800-476-3774**

E-mail us at sales@viscount.com or visit us at www.viscount.com

Viscount is a publicly traded company. For more information go to NASDAQ.com and enter ticker symbol 'VSYS'

