

KCV-350/KC-D32



FEATURES AND CHARACTERISTICS



Audio + video conversation with visitor



Door open function. Door release from camera (KC-D32, metal pinhole camera)



Up to 2 monitors & 1 camera connection



Compact size, convenient design and easy installation (mount on the wall or desk)

SPECIFICATION

Video Phone	KCV-350
Power	KCV-350 : SMPS AC100V ~ AC240V , Max. 10W, Stand by 1W
Assurance temperature	0°C ~ +50°C
Communication systems	One way hands free conversation
TFT LCD	3.5" Color TFT LCD
Wiring	4wires in polarity
Max. wiring distance	φ0.65 single cable : 50m, 5C-2V coaxial cable : 100m
Mount type	Surface mount
Dimension(mm)	112(W) x 176(H) x 43(D)
Weight (approx. kg)	1.2kgs
Camera	KC-D31 / KC-D32
Power	12V± 1V (power from monitor), Max. 2.5W
Image format	1/3" CCD, 270,000(NTSC) pixels
Lens	F:2.0, f=3.6mm
Camera angle	90°
Body material	Metal
Mim. illumination	0.1 lux on the object (IR LED ON)
Mount type	Surface mount
Dimension mm	(W)95 x (H)127 x (D)33
Monitor Connection	KC-D31(KIV-201C / KIV-202 / KIV-D202) / KC-D32(KCV-350 / KCV-D350)
Door lock connection	KC-D31 (Moniter) / KC-D32 (Camera)