

## Securitex Fire Safety Equipment Division

GB-2688 smoke and heat detector alarm was developed to provide portable application when implementing smoke and heat detection in open area. GB-2688 is battery operated as such it can be installed in area where power supply is not available and with built-in siren, there isn't a need to link the unit to any panel making the GB-2688 a truly standalone S&H detector.



**GB-2688**

Product Name : Smoke and Heat detector alarm  
Item NO : TYPE: GB-2688  
Smoke Alarm Detailed : Photoelectric smoke alarm with 9VDC battery

### **CEILING TYPE SMOKE ALARM WITH CE APPROVAL**

#### **ALARM Features:**

- Ceiling or wall mounting
- Easy to install with mounting hardware included
- 9VDC battery
- Suitable for any room
- Flash alarm indicator (red)
- Test button for easy recommended monthly testing
- Low battery signal
- Safety clip feature, not allow mounting of smoke alarm without battery installed
- Photoelectric chamber for early detection from all directions
- Loud 85dB alarm signal

#### **SPECIFICATIONS:**

Power Source : 9VDC battery  
Operating Current : 10mA (normal) and 20-50mA (alarm working)  
Sensitivity to smoke : In comply with UL217 & BS5446: Part 1 2000  
Kitemark License no : KM 53166. 0.81~1.42%/FT  
Operating Temperature : 40oF - 100oF (4. 4C - 37.8oC)  
Ambient Humidity : 10% - 90%.  
Horn Level : 85 Decibels at 10 feet.  
Battery life : 1 year min.  
Size : 110mmX25mm

Securitex Document No: USA.Securitex.GB-2688S&H-2008