



### STM 2460

#### technical specification


model:STM 2460

input voltage	220Vac - 240Vac 1 phase 50Hz
cranking power	350Amp
charging voltage	12Vdc - 24Vdc
charging current	1 - 60Amp (adjustable)
output	12V start - 4.2KW 24V start - 8.4KW
weight	51.5kg

- . A Mobile Charger / Starter designed for the garage and fleet
- . Operator with modern - style metal casing
- . Used as slow & fast charger and booster
- . Equipped with timer for fast charging and auto stop purposes
- . Selectable battery voltage range control (12V & 24V)
- . Input and output breaker protection
- . Variable and adjustable charging current control
- . Fitted with rubber wheels and handle for instant mobility
- . Build-in MCB against overloads and polarity

#### dimensions

model:STM 2460



### SMART 450

model:SMART 450

input voltage	220Vac - 240Vac 1 phase 50Hz
cranking power	450Amp
charging voltage	12Vdc - 24Vdc
charging current	1 - 60Amp (selectable)
output	12V start - 5.4KW 24V start - 10.8KW
weight	38kg

- . A Mobile starter / Charger designed for the garage and fleet
- . Operator with modern - style metal casing
- . Used as slow & fast charger and booster
- . Selectable battery voltage range (12V & 24V)
- . Input breaker protection
- . Selectable charging current control
- . Fitted with rubber wheels and handle for instant mobility
- . Robust in design and maintenance free
- . Easy to operate, reliable and economical

model:SMART 450

