

## Syris SY210NT2 / SY210NT4 Controller



**Low Cost - High Performance - Top Quality - Excellent Features**

**SY210NT2 / SY210NT4  
Controllers**



Controller Specifications		
Model / Part Number *	SY-210NT2	SY-210NT4
Number of cards	9,999	
Number of readers	4(2In,2Out)	8(4In,4Out)
Door control	2 door	4 door
Reader technologies	SYRIS RS485 format or Wiegand*	
User P.I.N code	4 digital code	
Input Points	Normally 4,Expandable to 32	
Control relay output	2 relay	4 relay
Communication ports	RS485, 2Ports(option RS232 x 1)	
Baud rate	4,800 bps - 115,200bps (default 19,200 bps) bauds	
Programmable time zone	60 time zones	
Group (application set)	16	
Holidays	366	
Controller ID	01-99	
Expand modules	SYRIS Serial module	
Anti-passback	Up to 3 levels of local and/or group anti-passback	
Keypad input	16 key keypad	
LCD display	16 x 2 LCD with backlight	
Speaker output	Maximum 0.2 W	
Indicator	8 LED	
Operating temperature	-10°C to 55 °C	
Storage temperature	-25 °C to 80°C	
Power supply input	DC 8V to 20V	
Power consumption	0.5W to 3W	
Dimensions (mm)	135W x 175H x 45D	

\*Wiegand Readers can only be used using the [SY-MDWIE1](#) multi-function module.

\*To order please use model / part number as in specification above.

\* This specification is preliminary and subject to change without prior notice.

For the above product literature and detail please download the full catalogue [here](#)

Securitex Electronic Systems Engineering Block 9010 Tampines St 93 #04-145 Singapore 528844 Tel:65-67852171 Fax:65-6786335