

i-Key 6 PIN/RX Quick Reference

1.0 Introduction

The i-Key 6 PIN/RX receiver has been designed to connect into a standard gate motor drive control system. The connection is made via a 6 way female connector on the i-key 6 PIN/RX which connects to the gate motor drive controller PCB.s 6 PIN male strip connector. Standard i-key TX pendants may be learnt into each 6 PIN/RX receiver (up to 250) to allow the user to operate the gate from the safety of a vehicle.

2.0 Programming

The receiver will be powered up once it is connected to the gate controller. To enter programming mode simply hold down the Programming Button for 2 seconds, the RED LED will now be on steady. To Exit programming mode, hold down the programming button for 2 seconds, the RED LED will now go out.

Adding i-Key TX

Once in programming mode simply press a button on each pendant that you want to be learnt in to the receiver. Each time a pendant is added the RED LED will flash once. Exit programming mode when all i-key pendants are learnt in. Once you are out of programming mode, you can press each i-key button to test if your i-Keys pendants are valid. Each time the i-Key 6 PIN/RX receives a valid i-key pendant transmission the GREEN LED will flash once.

Deleting the memory

The i-Key 6PIN/RX has a non volatile memory, so all programming remains in the memory even if power is removed from the board. To delete the memory simply hold down the programming button for 5 sec, the RED LED will then flash 5 times which indicates that the memory has now been erased.


i-Secure Customer Code

The receiver will use the i-Secure code of the first pendant learnt as its code. If an attempt is made to learn an i-Key pendant in with a different i-Secure code the RED LED will flash 3 times to indicate an invalid i-Secure customer code.

System Capacity

The capacity of the receiver is 250 pendants, when this limit is reached programming mode will automatically exit and the RED LED will flash 5 times.

The following show a i-key 6 pin Rx PCB layout and connector



iKey 6 Pin/ Rx 1