

Pan/tilt head and accessories



FH PTH 311 – pan tilt head

Maximum load: 12 kg, balanced
Horizontal speed: 6° / s
Vertical speed: 3° / s
Horizontal torque: 6 Nm
Vertical torque: 6 Nm
Autopan: contact controlled with delayed inversion
Power source: 24 V AC / 50 Hz
Power consumption: 7 W max.
Weatherproof rating: IP 66
Operating temperature: -20°C ~ +50°C
Material housing: aluminium
Colour: grey, RAL 9002
Dimensions: 279 (W) x 180 (H) x 161 (D) mm
Weight: 3,4 kg
Recommended housings: FH 7154, FH 7154 H, FH 7156, FH 7156 H
Mounting: wall mounting with BA PTAC,
pole mounting with BA PTAC + BA 15

FH PTH 311 P – pan tilt head with preset

Specifications see FH PTH 311, additionally:

Preset control: internal potentiometer for horizontal and vertical position

BA PTAC – wall mount bracket for pan tilt head



Material: aluminium
Colour: grey, RAL 9002
Length: 445 mm
Max. load: 50 kg

BA 15– pole mount adaptor WSFP



Pole diameter: 65 ~ 110 mm
Material: cast aluminium, stainless steel
Application: with BA 09, BA 12, BA PTAC